

Type: P3i



Features

Multimedia

3.5" TFT Screen support different Multimedia formats. Photo-ID Support the user's photo display and make T&A application more visible and rebible

Time & Attendance

Built-in backup battery protects data (optional)
Storage Capacity : store up to 10,000 templates (1:N) and 10,000 records.
More Practical function such as SMS, T9 input, Work-code enable user-friendly.
Offer a wide selection in authentication mode and easy security system upgrade with combination of fingerprint, password and ID/MIFARE/HID card.

Access Control

Monitor employee's movement at any time. Provide extra security with 50 time zone. User grouping, and professional unlocking combination function, easy integration with door lock system.

Communications

Versatile Interface options including RS232/485, TCP/IP, USB Host, USB Client, Optional WIFI and GPRS, Support WOOTIME System integrated Web base (Optional Required).

Introduction

Fingermatic P3i time attendance and access control terminal adopts latests technology and fingerprint algorithm to improve identification speed. It can manage 10,000 templates within 1 second (1:1 verification).

Fingermatic P3i features high performance, high image quality optical fingerprint sensor. The patented optical sensor is resistant to scratches, impact, vibration and electronic shock.

The Fingermatic P3i can be used in multi factor authentication that supports fingerprint, password, proximity, and smart card. It also has an option for Wi-Fi and GPRS connectivity.

The Fingermatic P3i has 3.5" color TFT-LCD display, so it can display the individual graphical interfaces and personel color photos. It comes standard with TCP/IP, RS-232/485, USB-host, USB-Client, 8 function keys, T9 input method, backup battery (optional) and has access control connectivity for Wiegand-in Wiegand-out, Door lock connection, Alarm, Bell, Remote to Exit switch.

Specification

Fingerprint Capacity	: 20,000 FP
Transaction Capacity	: 30,000 FP
Sensor	: Optical Sensor
ID	: 4 - 9 Digits
Communication	: RS232/485, TCP/IP, USB-Client, USB-Host, USB-Cable
Identification Time	: <= 1s
Matching Type	: 1 : 1 , 1 : N
Access Combination	: FP + Card + Password, FP / Card / Password
Integrated Communication	: Web base WOOTime support (optional)
Standard Function	: Workcode, SMS, DLST, Scheduled-bell, Self-Service Query Automatic Status Switch, T9 Input, Photo ID, Web Server, Built-in RFID Reader, built-in battery (optional), LAN Port
Access Control	: Lock, Door Sensor, Exit Button, Alarm, Door Bell
Interface for	: Anti-Pass Back
Wiegand Signal	: Input & Output
Optional Functions	: ID / Mifare / HID, Printer, Soap, WIFI, GPRS, RIS
Display	: 3.5 Inch TFT Screen
Power Supply	: 12V DC3A
Operating Temperature	: 0°C - 45°C
Operating Humidity	: 20% - 80%g
Dimension	: 213 x 178.2 x 47.5 mm
Weight	: 2.05 Kg

Configuration



Authorized Dealer :



*Subject and specification are subject to change without notice.